



ОТВЕРСТИЯ ПОД РЕЗЬБЫ – ŚREDNICE OTWORÓW


M DIN 13, ISO 261, *5H / 6H

Ø	P	Внутренний диаметр гайки Średnica otworu			
		Ø mini	Ø maxi	Ø guide line	
d _i	mm				
* 1	0.25	0.729	0.785	0.75	
* 1.1	0.25	0.829	0.885	0.85	
* 1.2	0.25	0.929	0.985	0.95	
* 1.4	0.30	1.075	1.142	1.10	
1.6	0.35	1.221	1.321	1.25	
1.7	0.35	1.321	1.421	1.35	
1.8	0.35	1.421	1.521	1.45	
2	0.40	1.567	1.679	1.60	
2.2	0.45	1.713	1.838	1.75	
2.3	0.40	1.867	1.979	1.90	
2.5	0.45	2.013	2.138	2.05	
2.6	0.45	2.113	2.238	2.15	
3	0.50	2.459	2.599	2.50	
3.5	0.60	2.850	3.010	2.90	
4	0.70	3.242	3.422	3.30	
4.5	0.75	3.688	3.878	3.75	
5	0.80	4.134	4.334	4.20	
6	1.00	4.917	5.153	5.00	
7	1.00	5.917	6.153	6.00	
8	1.25	6.647	6.912	6.80	
9	1.25	7.647	7.912	7.80	
10	1.50	8.376	8.676	8.50	
11	1.50	9.376	9.676	9.50	
12	1.75	10.106	10.441	10.20	
14	2.00	11.835	12.210	12.00	
16	2.00	13.835	14.210	14.00	
18	2.50	15.294	15.744	15.50	
20	2.50	17.294	17.744	17.50	
22	2.50	19.294	19.744	19.50	
24	3.00	20.752	21.252	21.00	
27	3.00	23.752	24.252	24.00	
30	3.50	26.211	26.771	26.50	
33	3.50	29.211	29.771	29.50	
36	4.00	31.670	32.270	32.00	
39	4.00	34.670	35.270	35.00	
42	4.50	37.129	37.799	37.50	
45	4.50	40.129	40.799	40.50	
48	5.00	42.587	43.297	43.00	
52	5.00	46.587	47.297	47.00	
56	5.50	50.046	50.796	50.50	

MF DIN 13, ISO 261, 6H

Ø	P	Внутренний диаметр гайки Średnica otworu			
		Ø mini	Ø maxi	Ø guide line	
d _i	mm				
8	1.00	6.917	7.153	7.00	
9	0.75	8.188	8.378	8.25	
9	1.00	7.917	8.153	8.00	
10	0.75	9.188	9.378	9.25	
10	1.00	8.917	9.153	9.00	
10	1.25	8.647	8.912	8.80	
11	0.75	10.188	10.378	10.25	
11	1.00	9.917	10.153	10.00	
12	1.00	10.917	11.153	11.00	
12	1.25	10.647	10.912	10.80	
12	1.50	10.376	10.676	10.50	
14	1.00	12.917	13.153	13.00	
14	1.25	12.647	12.912	12.80	
14	1.50	12.376	12.676	12.50	
15	1.00	13.917	14.153	14.00	
15	1.50	13.376	13.676	13.50	
16	1.00	14.917	15.153	15.00	
16	1.50	14.376	14.676	14.50	
17	1.00	15.917	16.153	16.00	
17	1.50	15.376	15.676	15.50	
18	1.00	16.917	17.153	17.00	
18	1.50	16.376	16.676	16.50	
18	2.00	15.835	16.210	16.00	
20	1.00	18.917	19.153	19.00	
20	1.50	18.376	18.676	18.50	
20	2.00	17.835	18.210	18.00	
22	1.00	20.917	21.153	21.00	
22	1.50	20.376	20.676	20.50	
22	2.00	19.835	20.210	20.00	
24	1.00	22.917	23.153	23.00	
24	1.50	22.376	22.676	22.50	
24	2.00	21.835	22.210	22.00	
25	1.00	23.917	24.153	24.00	
25	1.50	23.376	23.676	23.50	
25	2.00	22.835	23.210	23.00	
27	1.50	25.376	25.676	25.50	
27	2.00	24.835	25.210	25.00	
28	1.00	26.917	27.153	27.00	
28	1.50	26.376	26.676	26.50	
28	2.00	25.835	26.210	26.00	
30	1.00	28.917	29.153	29.00	
30	1.50	28.376	28.676	28.50	
30	2.00	27.835	28.210	28.00	
32	1.50	30.376	30.676	30.50	
32	2.00	29.835	30.210	30.00	
33	1.50	31.376	31.676	31.50	
33	2.00	30.835	31.210	31.00	
35	1.50	33.376	33.676	33.50	
36	1.50	34.376	34.676	34.50	
36	2.00	33.835	34.210	34.00	
36	3.00	32.752	33.252	33.00	
39	1.50	37.376	37.676	37.50	
39	2.00	36.835	37.210	37.00	
39	3.00	35.752	36.252	36.00	
40	1.50	38.376	38.676	38.50	

MF DIN 13, ISO 261, 6H

Ø	P	Внутренний диаметр гайки Średnica otworu			
		Ø mini	Ø maxi	Ø guide line	
d _i	mm				
2.5	0.35	2.121	2.221	2.15	
3	0.35	2.621	2.721	2.65	
3.5	0.35	3.121	3.221	3.15	
4	0.50	3.459	3.599	3.50	
4.5	0.50	3.959	4.099	4.00	
5	0.50	4.459	4.599	4.50	
5.5	0.50	4.959	5.099	5.00	
6	0.75	5.188	5.378	5.25	
7	0.75	6.188	6.378	6.25	
8	0.75	7.188	7.378	7.25	

