



# ОТВЕРСТИЯ ПОД РЕЗЬБЫ – ŚREDNICE OTWORÓW


## MF DIN 13, ISO 261, 6H

Ø	P	Внутренний диаметр гайки Średnica otworu			
		Ø mini	Ø maxi	Ø guide line	
d <sub>1</sub>	mm				
40	2.00	37.835	38.210	38.00	
40	3.00	36.752	37.252	37.00	
42	1.50	40.376	40.676	40.50	
42	2.00	39.835	40.210	40.00	
42	3.00	38.752	39.252	39.00	
45	1.50	43.376	43.676	43.50	
45	2.00	42.835	43.210	43.00	
45	3.00	41.752	42.252	42.00	
48	1.50	46.376	46.676	46.50	
48	2.00	45.835	46.210	46.00	
48	3.00	44.752	45.252	45.00	
50	1.50	48.376	48.676	48.50	
50	2.00	47.835	48.210	48.00	
50	3.00	46.752	47.252	47.00	
52	1.50	50.376	50.676	50.50	
52	2.00	49.835	50.210	50.00	
52	3.00	48.752	49.252	49.00	
55	2.00	52.835	53.210	53.00	
60	2.00	57.835	58.210	58.00	


## MF EN 60423:1994, 7H

Ø	P	Внутренний диаметр гайки Średnica otworu			
		Ø mini	Ø maxi	Ø guide line	
d <sub>1</sub>	mm				
8	1.00	6.917	7.217	7.00	
10	1.00	8.917	9.217	9.00	
12	1.50	10.376	10.751	10.50	
16	1.50	14.376	14.751	14.50	
20	1.50	18.376	18.751	18.50	
25	1.50	23.376	23.751	23.50	
32	1.50	30.376	30.751	30.50	
40	1.50	38.376	38.751	38.50	
63	1.50	61.376	61.751	61.50	


## UNC ANSI B1.1, 2B

Ø	P	P	Внутренний диаметр гайки Średnica otworu			
			Ø mini	Ø maxi	Ø guide line	
d <sub>1</sub>	TPI	mm				
1	64	0.397	1.425	1.582	1.45	
2	56	0.454	1.695	1.871	1.75	
3	48	0.529	1.941	2.146	2.00	
4	40	0.635	2.157	2.385	2.25	
5	40	0.635	2.487	2.697	2.55	
6	32	0.794	2.642	2.895	2.75	
8	32	0.794	3.302	3.530	3.40	
10	24	1.058	3.683	3.962	3.80	
12	24	1.058	4.344	4.597	4.40	
1/4"	20	1.270	4.979	5.257	5.10	
5/16"	18	1.411	6.401	6.731	6.50	

## UNC ANSI B1.1, 2B

Ø	P	P	Внутренний диаметр гайки Średnica otworu			
			Ø mini	Ø maxi	Ø guide line	
d <sub>1</sub>	TPI	mm				
3/8"	16	1.588	7.798	8.153	8.00	
7/16"	14	1.814	9.144	9.550	9.30	
1/2"	13	1.954	10.592	11.023	10.80	
9/16"	12	2.117	11.989	12.446	12.20	
5/8"	11	2.309	13.386	13.868	13.60	
3/4"	10	2.540	16.307	16.840	16.60	
7/8"	9	2.822	19.177	19.761	19.50	
1"	8	3.175	21.971	22.606	22.30	
1 1/8"	7	3.629	24.638	25.349	25.00	
1 1/4"	7	3.629	27.813	28.524	28.20	
1 3/8"	6	4.233	30.353	31.115	30.80	
1 1/2"	6	4.233	33.528	34.290	34.00	
1 3/4"	5	5.080	38.964	39.827	39.50	
2"	4.5	5.644	44.679	45.593	45.30	

## UNJC ISO 3161:1999, 3B

Ø	P	P	Внутренний диаметр гайки Średnica otworu			
			Ø mini	Ø maxi	Ø guide line	
d <sub>1</sub>	TPI	mm				
4	40	0.635	2.228	2.393	2.30	
5	40	0.635	2.558	2.723	2.60	
6	32	0.794	2.733	2.939	2.80	
8	32	0.794	3.393	3.599	3.45	
10	24	1.058	3.795	4.064	3.90	
12	24	1.058	4.455	4.704	4.55	
1/4"	20	1.270	5.113	5.387	5.20	
5/16"	18	1.411	6.563	6.833	6.70	
3/8"	16	1.588	7.978	8.255	8.10	
7/16"	14	1.814	9.347	9.639	9.40	
1/2"	13	1.954	10.798	11.095	10.90	
9/16"	12	2.117	12.228	12.482	12.40	
5/8"	11	2.309	13.627	13.904	13.80	
3/4"	10	2.540	16.576	16.881	16.70	