



ДИАМЕТРЫ ПОД ПЛАШКИ – ŚREDNICE WAŁKÓW


UN ANSI B1.1, 2A

Ø	P	P	Наружный диаметр резьбы			
			Średnica zewnętrzna			
d _i	TPI	mm	Ø mini	Ø maxi	Ø guide line	
5/16"	20	1.270	7.702	7.907	7.80	
3/8"	20	1.270	9.289	9.494	9.39	
9/16"	20	1.270	14.049	14.254	14.15	
5/8"	20	1.270	15.637	15.841	15.74	
1 1/8"	8	3.175	28.141	28.521	28.33	
1 1/4"	8	3.175	31.316	31.696	31.51	
1 3/8"	8	3.175	34.489	34.869	34.68	
1 1/2"	8	3.175	37.664	38.044	37.85	
1 5/8"	8	3.175	40.839	41.219	41.03	
1 3/4"	8	3.175	44.011	44.391	44.20	
1 7/8"	8	3.175	47.186	47.566	47.38	
2"	8	3.175	50.361	50.741	50.55	
2 1/4"	8	3.175	56.709	57.089	56.90	
2 1/2"	8	3.175	63.059	63.439	63.25	
2 3/4"	8	3.175	69.406	69.786	69.60	
3"	8	3.175	75.753	76.133	75.94	


W (BSW) BS 84

Ø	P	P	Наружный диаметр резьбы			
			Średnica zewnętrzna			
d _i	TPI	mm	Ø mini	Ø maxi	Ø guide line	
1/4"	20	1.270	6.165	6.319	6.24	
5/16"	18	1.411	7.737	7.904	7.82	
3/8"	16	1.588	9.312	9.489	9.40	
7/16"	14	1.814	10.884	11.074	10.98	
1/2"	12	2.117	12.456	12.662	12.56	
5/8"	11	2.309	15.613	15.832	15.72	
3/4"	10	2.540	18.771	19.004	18.89	
7/8"	9	2.822	21.979	22.225	22.10	
1"	8	3.175	25.138	25.400	25.27	
1 1/8"	7	3.629	28.296	28.575	28.44	
1 1/4"	7	3.629	31.465	31.750	31.61	
1 1/2"	6	4.233	37.793	38.100	37.95	
1 3/4"	5	5.080	44.117	44.450	44.28	
2"	4.5	5.644	50.449	50.800	50.62	
2 1/4"	4	6.350	56.779	57.150	56.96	
2 1/2"	4	6.350	63.119	63.500	63.31	


UNS ANSI B1.1, 2A

Ø	P	P	Наружный диаметр резьбы			
			Średnica zewnętrzna			
d _i	TPI	mm	Ø mini	Ø maxi	Ø guide line	
10	36	0.706	4.664	4.803	4.73	
10	40	0.635	4.674	4.803	4.74	
10	56	0.454	4.705	4.808	4.76	
1/4"	36	0.706	6.188	6.327	6.26	
1/4"	40	0.635	6.198	6.327	6.26	
1/4"	48	0.529	6.216	6.329	6.27	
1/4"	56	0.454	6.226	6.329	6.28	
5/16"	36	0.706	7.775	7.914	7.84	
3/8"	36	0.706	9.360	9.499	9.43	
7/16"	24	1.058	10.902	11.084	10.99	
1/2"	24	1.058	12.487	12.669	12.58	
1"	14	1.814	25.096	25.356	25.23	


PG DIN 40430

Ø	P	P	Наружный диаметр резьбы			
			Średnica zewnętrzna			
d _i	TPI	mm	Ø mini	Ø maxi	Ø guide line	
7	20	1.270	12.3	12.5	12.40	
9	18	1.411	15.0	15.2	15.10	
11	18	1.411	18.4	18.6	18.50	
13.5	18	1.411	20.2	20.4	20.30	
16	18	1.411	22.3	22.5	22.40	
21	16	1.588	28.0	28.3	28.15	
29	16	1.588	36.7	37.0	36.85	
36	16	1.588	46.7	47.0	46.85	
42	16	1.588	53.7	54.0	53.85	
48	16	1.588	59.0	59.3	59.15	

G (BSP) DIN ISO 228

Ø	P	P	Наружный диаметр резьбы			
			Średnica zewnętrzna			
d _i	TPI	mm	Ø mini	Ø maxi	Ø guide line	
1/16"	28	0.907	7.509	7.723	7.62	
1/8"	28	0.907	9.514	9.728	9.62	
1/4"	19	1.337	12.907	13.157	13.03	
3/8"	19	1.337	16.412	16.662	16.54	
1/2"	14	1.814	20.671	20.955	20.81	
5/8"	14	1.814	22.627	22.911	22.77	
3/4"	14	1.814	26.157	26.441	26.30	
7/8"	14	1.814	29.917	30.201	30.06	
1"	11	2.309	32.889	33.249	33.07	
1 1/8"	11	2.309	37.537	37.897	37.72	
1 1/4"	11	2.309	41.550	40.910	41.73	
1 3/8"	11	2.309	43.963	44.323	44.14	
1 1/2"	11	2.309	47.443	47.803	47.62	
1 3/4"	11	2.309	53.386	53.746	53.57	
2"	11	2.309	59.254	59.614	59.43	
2 1/4"	11	2.309	65.276	65.710	65.49	
2 1/2"	11	2.309	74.750	75.184	74.97	
2 3/4"	11	2.309	81.100	81.534	81.32	
3"	11	2.309	87.450	87.884	87.67	
3 1/2"	11	2.309	99.896	100.330	100.11	

TR ISO 2901-2904, DIN 103, 7e

Ø	P	Наружный диаметр резьбы			
		Średnica zewnętrzna			
d _i	mm	Ø mini	Ø maxi	Ø guide line	
10	2	9.820	10.000	9.91	
12	3	11.764	12.000	11.88	
14	3	13.764	14.000	13.88	
16	4	15.700	16.000	15.85	
18	4	17.700	18.000	17.85	
20	4	19.700	20.000	19.85	
22	5	21.665	22.000	21.83	
24	5	23.665	24.000	23.83	
26	5	25.665	26.000	25.83	
28	5	27.665	28.000	27.83	
30	6	29.625	30.000	29.81	
32	6	31.625	32.000	31.81	

